

General purpose SMT chip tantalum series General low power DC/DC and LDO Operating Standard: QJ/PWV109-2003 Military Parts Qualified Factory RoHS & REACH compliance Specifications Operating Temperature Range: -55 °C ~ ...

Chip Multilayer Ceramic Capacitors for General Purpose GRM022C71A103KE01_(0402M(01005), X7S(EIA), 10000pF, DC 10V) _:Package Reference Sheet Product specifications in this catalog are as of Dec.23,2021, and are subject to change or obsolescence without notice. Please consult the approval sheet before ordering. Please read ...

Chip Multilayer Ceramic Capacitors for General Purpose GRM32ER61C226KE20_(3225M(1210), X5R(EIA), 22uF, DC 16V) _:Package Reference Sheet Product specifications in this catalog are as of Nov.4,2021, and are subject to change or obsolescence without notice. Please consult the approval sheet before ordering. Please read rating and !Cautions first ...

Würth Elektronik WCAP-CSGP General-Purpose MLCCs ceramic characteristics of Class I and Class II. Class I ceramic capacitors, which include the NPO type, are characterized by a small ...

General Purpose, Capacitors manufactured by Vishay, a global leader for semiconductors and passive electronic components.

Purpose Multilayer Ceramic Chip Capacitors General 8-2. 1210, 1812, 1825, 2220, 2225 Sizes DIELECTRIC X7R SIZE 1210 1812 1825 2220 2225 (VDC) 6.3V 10V 16V 25V 50V 10V 16V 25V 50V 50V 50V 50V

Chip Multilayer Ceramic Capacitors for General Purpose Specifications and Test Methods (Operating Temp. Range) Temp. coeff or Cap. Change ±10 % (8) Packaging (6) Capacitance Tolerance 1 uF 0.3 min. (1)-1 L 1.0±0.1 (1)-2 W 0.5±0.1 This product specification is applied to Chip Multilayer Ceramic Capacitors used for General Electronic equipment ...

General purpose chip resistors ... Capacitors Film capacitor selection tool Polymer and electrolytic capacitor selection tool ...

General Purpose & High Cap. X7R Surface-Mount Ceramic Multilayer Capacitors 6.3 V to 250 V SCOPE This specification describes X7R series chip capacitors with lead-free terminations. APPLICATIONS PCs, Hard disk, Game PCs DVDs, Video cameras Mobile phones Data processing FEATURES Supplied in tape on reel

Features & Benefits. Voltage Range: 10V to 2000V; Capacitance Range: 0.01uF to 22uF; Dielectrics: NP0,

X7R, X5R, Z5U, Y5V; Case Sizes: 0402 to 2225; Tape & Reel Packaging

Surface-Mount Ceramic Multilayer Capacitors 23 Product specification General Purpose 16 V to 250 V 0 CAP.

Web: <https://www.vielec-electricite.fr>